

Exoset - Vertical lifting clamp

Suitable for lifting, vertical transport, turning 180° moving and vertical transfer of sheet, plates and constructions.

Item Name short	Jaw Opening Width [in]	Weight Net [lbs]	WLL Vertical [lbs]	Dimension A [in]	Dimension B [in]	Dimension C [in]	Dimension D [in]
0.5t EVU	0 - 0.63	4.19	1100	1.54	8.22	5.27	1.57
0.5t EVU/J	0.59 - 1.18	4.19	1100	1.54	8.91	5.29	1.59
0.5t EVU/H	0 - 0.63	4.19	1100	1.54	8.91	5.29	1.59
0.5t EVU/S	0 - 0.63	4.19	1100	1.54	8.91	5.29	1.59
0.5t EVU/HJ	0.59 - 1.18	4.41	1100	1.54	8.91	5.29	1.59
0.5t EVU/SJ	0.59 - 1.18	4.41	1100	1.54	8.91	5.29	1.59
1t EVU	0 - 0.79	4.63	2204	1.54	9.35	5.73	2.06
1t EVU/H	0 - 0.79	4.63	2204	1.54	9.35	5.73	2.06
1t EVU/S	0 - 0.79	4.63	2204	1.54	9.35	5.73	2.06
1t EVU/J	0.79 - 2.75	5.73	2204	1.54	9.35	5.73	2.06
1t EVU/HJ	0.79 - 2.75	5.73	2204	1.54	9.35	5.73	2.06
1t EVU/SJ	0.79 - 2.75	5.73	2204	1.54	9.35	5.73	2.06
2t EVU	0 - 1.38	16.75	4409	2.68	14.78	8.24	2.99
2t EVU/H	0 - 1.38	16.75	4409	2.68	14.78	8.24	2.99
2t EVU/S	0 - 1.38	16.75	4409	2.68	14.78	8.24	2.99
2t EVU/J	1.38 - 2.75	19.62	4409	2.68	14.78	8.24	2.99
2t EVU/HJ	1.38 - 2.75	19.62	4409	2.68	14.78	8.24	2.99
2t EVU/SJ	1.38 - 2.75	19.62	4409	2.68	14.78	8.24	2.99
3t EVU/J	1.57 - 3.15	30.2	6613	2.87	17.56	10.34	4.01
3t EVU/HJ	1.57 - 3.15	30.2	6613	2.87	17.56	10.34	4.01
3t EVU/SJ	1.57 - 3.15	30.2	6613	2.87	17.56	10.34	4.01
3t EVU	0 - 0.79	32.63	6613	2.87	17.56	10.34	4.01
3t EVU/H	0 - 1.57	32.63	6613	2.87	17.56	10.34	4.01
3t EVU/S	0 - 1.57	32.63	6613	2.87	17.56	10.34	4.01
5t EVU	0 - 1.57	35.27	11023	2.87	17.56	10.34	4.01



Item Name short	Jaw Opening Width [in]	Weight Net [lbs]	WLL Vertical [lbs]	Dimension A [in]	Dimension B [in]	Dimension C [in]	Dimension D [in]
5t EVU/H	0 - 1.57	35.27	11023	2.87	17.56	10.34	4.01
5t EVU/S	0 - 1.57	35.27	11023	2.87	17.56	10.34	4.01
5t EVU/J	1.57 - 3.15	36.16	11023	2.87	17.56	10.34	4.01
5t EVU/HJ	1.57 - 3.15	36.16	11023	2.87	17.56	10.34	4.01
5t EVU/SJ	1.57 - 3.15	36.16	11023	2.87	17.56	10.34	4.01
6t EVU	0 - 1.97	52.91	13227	3.15	21.64	12.89	5.19
6t EVU/H	0 - 1.97	52.91	13227	3.15	21.64	12.89	5.19
6t EVU/S	0 - 1.97	52.91	13227	3.15	21.64	12.89	5.19
6t EVU/J	1.97 - 3.94	54.9	13227	3.15	21.64	12.89	5.19
6t EVU/HJ	1.97 - 3.94	54.9	13227	3.15	21.64	12.89	5.19
6t EVU/SJ	1.97 - 3.94	54.9	13227	3.15	21.64	12.89	5.19

Item Name short	Dimension E [in]	Dimension F [in]	Dimension G [in]	Dimension H [in]	For Material	Dimension I [in]	Dimension J [in]
0.5t EVU	1.73	0.86	4.33	0.51	Normal max.37HRC	0.78	1.10
0.5t EVU/J	1.63	0.88	4.49	0.53	Normal max.37HRC	0.8	1.12
0.5t EVU/H	1.63	0.88	4.49	0.53	Hard max.47HRC	0.8	1.12
0.5t EVU/S	1.63	0.88	4.49	0.53	Stainless Steel max.37HRC	0.8	1.12
0.5t EVU/HJ	1.63	0.88	4.49	0.53	Hard max.47HRC	0.8	1.12
0.5t EVU/SJ	1.63	0.88	4.49	0.53	Stainless Steel max.37HRC	0.8	1.12
1t EVU	1.74	1.12	5	0.53	Normal max.37HRC	0.80	1.12
1t EVU/H	1.74	1.12	5	0.53	Hard max.47HRC	0.80	1.12
1t EVU/S	1.74	1.12	5	0.53	Stainless Steel max.37HRC	0.80	1.12



Item Name short	Dimension E [in]	Dimension F [in]	Dimension G [in]	Dimension H [in]	For Material	Dimension I [in]	Dimension J [in]
1t EVU/J	1.74	1.12	5	0.53	Normal max.37HRC	0.8	1.12
1t EVU/HJ	1.74	1.12	5	0.53	Hard max.47HRC	0.8	1.12
1t EVU/SJ	1.74	1.12	5	0.53	Stainless Steel max.37HRC	0.8	1.12
2t EVU	2.43	1.9	7.58	0.71	Normal max.37HRC	1.26	1.73
2t EVU/H	2.43	1.9	7.58	0.71	Hard max.47HRC	1.26	1.73
2t EVU/S	2.43	1.9	7.58	0.71	Stainless Steel max.37HRC	1.26	1.73
2t EVU/J	2.43	1.9	7.58	0.71	Normal max.37HRC	1.26	1.73
2t EVU/HJ	2.43	1.9	7.58	0.71	Hard max.47HRC	1.26	1.73
2t EVU/SJ	2.43	1.9	7.58	0.71	Stainless Steel max.37HRC	1.26	1.73
3t EVU/J	2.8	2.17	8.85	0.9	Normal max.37HRC	1.65	2.28
3t EVU/HJ	2.8	2.17	8.85	0.9	Hard max.47HRC	1.65	2.28
3t EVU/SJ	2.8	2.17	8.85	0.9	Stainless Steel max.37HRC	1.65	2.28
3t EVU	2.8	2.17	8.85	0.9	Normal max.37HRC	1.65	2.28
3t EVU/H	2.8	2.17	8.85	0.9	Hard max.47HRC	1.65	2.28
3t EVU/S	2.8	2.17	8.85	0.9	Stainless Steel max.37HRC	1.65	2.28
5t EVU	2.8	2.17	8.85	0.9	Normal max.37HRC	1.65	2.44
5t EVU/H	2.8	2.17	8.85	0.9	Hard max.47HRC	1.65	2.44
5t EVU/S	2.8	2.17	8.85	0.9	Stainless Steel max.37HRC	42	2.44



Item Name short	Dimension E [in]	Dimension F [in]	Dimension G [in]	Dimension H [in]	For Material	Dimension I [in]	Dimension J [in]
5t EVU/J	2.8	2.17	8.85	0.9	Normal max.37HRC	1.65	2.44
5t EVU/HJ	2.8	2.17	8.85	0.9	Hard max.47HRC	1.65	2.44
5t EVU/SJ	2.8	2.17	8.85	0.9	Stainless Steel max.37HRC	1.65	2.44
6t EVU	2.84	2.32	11.06	1.46	Normal max.37HRC	1.65	2.44
6t EVU/H	2.84	2.32	11.06	1.46	Hard max.47HRC	1.65	2.44
6t EVU/S	2.84	2.32	11.06	1.46	Stainless Steel max.37HRC	1.65	2.44
6t EVU/J	2.84	2.32	11.06	1.46	Normal max.37HRC	1.65	2.44
6t EVU/HJ	2.84	2.32	11.06	1.46	Hard max.47HRC	1.65	2.44
6t EVU/SJ	2.84	2.32	11.06	1.46	Stainless Steel max.37HRC	1.65	2.44



ORDER NUMBERS[Global Item Number/Local ERP Number SSUS]

WLL Vertical	For Material	Jaw Opening Width	0.5 t	1 t	2 t	3 t	5 t	6 t
0 - 0.63 in	Normal max.37HRC	0 - 16 mm	2002421 2002421	-	-	-	-	-
0.59 - 1.18 in	Normal max.37HRC	15 - 30 mm	2030330	-	-	-	-	-
0 - 0.63 in	Stainless Steel max.37HRC	0 - 16 mm	2012567 2012567	-	-	-	-	-
0.59 - 1.18 in	Stainless Steel max.37HRC	15 - 30 mm	2030342	-	-	-	-	-
0 - 0.63 in	Hard max.47HRC	0 - 16 mm	2012561 2012561	-	-	-	-	-
0.59 - 1.18 in	Hard max.47HRC	15 - 30 mm	2030336	-	-	-	-	-
0 - 0.79 in	Normal max.37HRC	0 - 20 mm	-	2002422 2002422	-	-	-	-
0.79 - 2.75 in	Normal max.37HRC	20 - 40 mm	-	2030331	-	-	-	-
0 - 0.79 in	Stainless Steel max.37HRC	0 - 20 mm	-	2012568 2012568	-	-	-	-
0.79 - 2.75 in	Stainless Steel max.37HRC	20 - 40 mm	-	2030343	-	-	-	-
0 - 0.79 in	Hard max.47HRC	0 - 20 mm	-	2012562 2012562	-	-	-	-
0.79 - 2.75 in	Hard max.47HRC	20 - 40 mm	-	2030337	-	-	-	-
0 - 1.38 in	Normal max.37HRC	0 - 35 mm	-	-	2002423 2002423	-	-	-
1.38 - 2.75 in	Normal max.37HRC	35 - 70 mm	-	-	2030332	-	-	-
0 - 1.38 in	Stainless Steel max.37HRC	0 - 35 mm	-	-	2012569 2012569	-	-	-
1.38 - 2.75 in	Stainless Steel max.37HRC	35 - 70 mm	-	-	2030344	-	-	-
0 - 1.38 in	Hard max.47HRC	0 - 35 mm	-	-	2012563 2012563	-	-	-
1.38 - 2.75 in	Hard max.47HRC	35 - 70 mm	-	-	2030338	-	-	-
0 - 0.79 in	Normal max.37HRC	0 - 40 mm	-	-	-	2002424 2002424	-	-
1.57 - 3.15 in	Normal max.37HRC	40 - 80 mm	-	-	-	2030333	-	-
0 - 1.57 in	Stainless Steel max.37HRC	0 - 40 mm	-	-	-	2012570 2012570	-	-
1.57 - 3.15 in	Stainless Steel max.37HRC	40 - 80 mm	-	-	-	2030345	-	-
0 - 1.57 in	Hard max.47HRC	0 - 40 mm	-	-	-	2012564 2012564	-	-
1.57 - 3.15 in	Hard max.47HRC	40 - 80 mm	-	-	-	2030339	-	-
0 - 1.57 in	Normal max.37HRC	0 - 40 mm	-	-	-	-	2002425 2002425	-
1.57 - 3.15 in	Normal max.37HRC	40 - 80 mm	-	-	-	-	2030334	-



WLL Vertical	For Material	Jaw Opening Width	0.5 t	1 t	2 t	3 t	5 t	6 t
0 - 1.57 in	Stainless Steel max.37HRC	0 - 40 mm	-	-	-	-	2012571 2012571	-
1.57 - 3.15 in	Stainless Steel max.37HRC	40 - 80 mm	-	-	-	-	2030346	-
0 - 1.57 in	Hard max.47HRC	0 - 40 mm	-	-	-	-	2012565 2012565	-
1.57 - 3.15 in	Hard max.47HRC	40 - 80 mm	-	-	-	-	2030340	-
0 - 1.97 in	Normal max.37HRC	0 - 50 mm	-	-	-	-	-	2002426 2002426
1.97 - 3.94 in	Normal max.37HRC	50 - 100 mm	-	-	-	-	-	2030335
0 - 1.97 in	Stainless Steel max.37HRC	0 - 50 mm	-	-	-	-	-	2012572 2012572
1.97 - 3.94 in	Stainless Steel max.37HRC	50 - 100 mm	-	-	-	-	-	2030347
0 - 1.97 in	Hard max.47HRC	0 - 50 mm	-	-	-	-	-	2012566 2012566
1.97 - 3.94 in	Hard max.47HRC	50 - 100 mm	-	-	-	-	-	2030341

■ Norms EN 13155 ASME B30.20 DNV GL

■ Packaging Unit (PU) Content 1

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of
America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**