



PowerLift Type 3 (EE) Flat Eye and Eye

Lifting slings

Item Name short	Weight Net [lbs]	WLL Vertical [lbs]	Length [ft.]	WLL Choker [lbs]	WLL 90° Basket lbs [lbs]	Belt Layers	Minimum Length [ft.]
EE2701X3	0.4	3100	3	2480	6200	2	3
EE1701X3	0.6	1600	3	1280	3200	-	3
EE1702X3	0.65	3200	3	2560	6400	-	3
EE1701X4	0.73	1600	4	1280	3200	-	3
EE1702X4	0.78	3200	4	2560	6400	-	3
EE2701X6	0.8	3100	6	2480	6200	2	3
EE1701X6	0.85	1600	6	1280	3200	-	3
EE2702X3	0.86	6400	3	5120	12800	-	6
EE2702X3P	0.86	6400	3	5120	12800	2	6
EE1702X6	0.9	3200	6	2560	6400	-	3
EE1701X10	0.98	1600	10	1280	3200	-	3
EE2701X10	1.35	3100	10	2480	6200	2	3
EE1702X10	1.35	3200	10	2560	6400	-	3
EE2702X6P	1.38	6400	6	5120	12800	2	6
EE2702X6	1.55	6400	6	5120	12800	-	6
EE2702X10P	2.5	6400	10	5120	12800	2	6
EE2704X6	2.65	11500	6	9200	23000	-	6
EE2702X12	2.9	6400	12	5120	12800	-	6
EE2702X12P	2.9	6400	12	5120	12800	2	6
EE2704X10	3.65	11500	10	9200	23000	-	6

Item Name short	Minimum Eye Length [in]	Width [in]	Main Material
EE2701X3	12	1	Nylon
EE1701X3	12	1	Nylon
EE1702X3	12	2	Nylon
EE1701X4	12	1	Nylon
EE1702X4	12	2	Nylon
EE2701X6	12	1	Nylon
EE1701X6	12	1	Nylon
EE2702X3	12	2	Nylon



Item Name short	Minimum Eye Length [in]	Width [in]	Main Material
EE2702X3P	12	2	Polyester
EE1702X6	12	2	Nylon
EE1701X10	12	1	Nylon
EE2701X10	12	1	Nylon
EE1702X10	12	2	Nylon
EE2702X6P	12	2	Polyester
EE2702X6	12	2	Nylon
EE2702X10P	12	2	Polyester
EE2704X6	23	4	Nylon
EE2702X12	12	2	Nylon
EE2702X12P	12	2	Polyester
EE2704X10	23	4	Nylon

ORDER NUMBERS

Length	WLL Vertical	Nylon	Polyester
3 ft.	1600 lbs	2024490	-
3 ft.	3100 lbs	2024515	-
3 ft.	3200 lbs	2024511	-
3 ft.	6400 lbs	2024518	2024675
4 ft.	1600 lbs	2024491	-
4 ft.	3200 lbs	2024512	-
6 ft.	1600 lbs	2024492	-
6 ft.	3100 lbs	2024516	-
6 ft.	3200 lbs	2024513	-
6 ft.	6400 lbs	2024519	2024522
6 ft.	11500 lbs	2024525	-
10 ft.	1600 lbs	2024493	-
10 ft.	3100 lbs	2024517	-
10 ft.	3200 lbs	2024514	-
10 ft.	6400 lbs	-	2024523
10 ft.	11500 lbs	2024526	-
12 ft.	6400 lbs	2024521	2024524

- Color Yellow
- Temperature Range -40°C bis +100°C

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of
America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**

■ Packaging Unit (PU) Content 1

